



**COMINOFF**

## **DEROGATION FOR 2014**

<b>Discipline</b>	Offshore, X-Cat
<b>Rule article n°</b>	part 4, rule 08.
<b>Subject</b>	Gearbox

### **2011-2013 RULE**

The water intake may be repositioned; it must however remain on the gear case torpedo. The width or height of the gear case torpedo must not be changed. The length fore and aft may be increased. The rear edge of the water intake opening must not be further back than 30% of the total length of the modified gear case torpedo.

The original intake to the circulation pump may be filled in and faired.

For cooling purposes it is allowed to add material in front of the union leg, as long as the union leg width is not increased, except where the union leg meets the lower side of the anti-cavitation plate.

The modification shall be for cooling purposes only and shall form a radius. The radius shall be lengthwise parallel to the anti-cavitation plate.

It is also permitted to add material to the centre section exhaust housing for the purpose of reducing noise.

Remote water pick-ups are not allowed.

Bearing carriers and propshafts may be changed from original.

All craft must be able to be maneuvered ahead and astern and have neutral capability, operated by controls at the helmsman's position. This facility must be a permanent installation and able to be demonstrated as practical at any time.

### **RULE TEXT FOR 2014 SEASON - NOT MODIFIED**

The water intake may be repositioned; it must however remain on the gear case torpedo. The width or height of the gear case torpedo must not be changed. The length fore and aft may be increased. The rear edge of the water intake opening must not be further back than 30% of the total length of the modified gear case torpedo.

The original intake to the circulation pump may be filled in and faired.

For cooling purposes it is allowed to add material in front of the union leg, as long as the union leg width is not increased, except where the union leg meets the lower side of the anti-cavitation plate.

The modification shall be for cooling purposes only and shall form a radius. The radius shall be lengthwise parallel to the anti-cavitation plate.

It is also permitted to add material to the centre section exhaust housing for the purpose of reducing noise.

Remote water pick-ups are not allowed.

Bearing carriers and propshafts may be changed from original.

All craft must be able to be maneuvered ahead and astern and have neutral capability, operated by controls at the helmsman's position. This facility must be a permanent installation and able to be demonstrated as practical at any time.

### **SIGNATURE**

**Monaco 22.01.2014**

**President of Cominoff  
Per Benson**